

Dual USB Charger Socket

IP 66 4.8Amp

Features

- ▶ Certified to Ip66 against dust and prolonged spray to withstand severe outdoor environments.
- ▶ The Dual USB Charger socket has ratings up to 4.8A (32VDC) and CE approval
- ▶ Over Voltage / Over Current / Short Circuit Protection
- ▶ Over Temperature / Reverse Polarity Protection
- ▶ Single Port Output Current : 2.4A DC
- ▶ 4.8 Amp 2 Port with Intelligent Device Detection
- ▶ LED color: Blue/Red/Green/Orange/White

Part # 3000-1001

Specification

Electrical

USB Type:	2.0
Number of USB Ports:	2
Normal Voltage:	12V / 24V DC
Operating Voltage:	8V / 32V (max)
Peak Voltage :	36V DC (max)(3~4seconds)
Output Voltage:	5V DC \pm 5%
Single Output Current:	2.4A DC
Max Output Current:	4.8A DC(max)
Current Draw:	Quiescent current: 20mA
Life:	5,000 operating cycles
Sealing:	IP66
Terminal:	Copper/nickel plating 1/4"
Operating Temperature:	-40°C ~ +60°C

Mounting

Panel Opening :	<input type="checkbox"/> 0.83" x 1.46"
	<input type="radio"/> Ø1.15"

Protection

Over Voltage Protection :	Yes
Over Current Protection :	Yes
Over Temperature Protection :	Yes
Short Circuit Protection :	Yes
Reverse Polarity Protection :	Yes

Product



Drawing

(in inch)

